

KPC133

14 LEDs Dome Camera



- FEATURES

- (1) High sensitivity in the dark environment, 0.3Lux / F2.0, 0Lux (IR ON)
- (2) Day and night features for 24-hour surveillance
- (3) Excellent image quality
- (4) IR LED effective range reaches up to 10 meters

- SPECIFICATIONS*

MODEL	KPC133
Pick up Element	1/3" color CCD image sensor
Number of Pixel	512(H) x 492(V) <NTSC> / 512(H) x 582(V) <PAL>
Resolution	420 TVL
Min. Illumination	0.3Lux (IR OFF)/ F2.0, 0Lux (IR ON)
IR LED	14 units
Effective Range	Up to 10 Meters
S/N Ratio	More than 48dB (AGC off)
Electronic Shutter	1/60 (1/50) to 1/100,000 sec.
Lens	f3.6mm / F2.0
Lens Angle	92.6°
IRIS Mode	AES
White Balance	ATW
Video Output	1.0 Vp-p composite, 75Ω
Power Source	DC12V
Current Consumption (±10%)	90mA (IR OFF), 210mA (IR ON)

* The specifications are subject to change without notice.

** Dimensional Tolerance: ± 5mm

Good Sensitivity in Low Illumination

KPC13x Series



Conventional



True Color

KPC13x Series



Conventional

